eppendorf



Increase Your Input – Expand Your Output

New high-capacity fixed-angle Rotor FA-6x250 for up to 6 imes 250 mL bottles

Rotor FA-6x250 extends the application range of large benchtop Centrifuge 5910 R and Centrifuge 5920 R. This includes harvesting of bacteria, algae and yeast, as well as mammalian cells in vessels up to 250 mL. A further scope of application is plasmid DNA extractions and lysate clearance after cell lysis.

A broad range of 12 different adapters minimizes the need of rotor exchanges during the workflow, since numerous vessel types with various volumes can be used with just a switch of adapters. This improves handling and saves time.

Applications

- > Pelleting of microorganisms
 - Bacteria
 - Yeast
 - Algae
- > Pelleting of mammalian cells
- > Purification of nucleic acids
- > Separation of protein precipitates
- > Clarification of supernatants
- > Separation of blood samples

eppendorf



Features & Benefits

- > High throughput: up to 6×250 mL bottles
- > Broad range of applications: 12 optional adapters
- > High speed: 15,054 × *g* (10,100 rpm)
- > Simple and fast handling: Eppendorf QuickLock® lid
- > Safe operation: aerosol-tight lid*
- > Stress-free work: low weight of only 5.3 kg
- > High chemical resistance: anodized aluminum
- > Low risk of contamination: rotor, lid and adapters autoclavable

* Aerosol-tightness tested by Public Health England, Porton Down, UK. Maximum 80% of maximum filling volume.



Ordering Information

Number of vessels per rotor	Order no.
6×250 mL flat bottom bottles ^{*1} or	5895 175 007

*¹ 250 mL flat bottom bottles from Nalgene[®] (3127-0250, 3122-0250, 3120-0250) and Corning[®] (431841, 431842). When used with wide lid 250 mL flat bottom bottle from Nalgene (3140-0250) max. capacity is reduced to 4 × 250 mL. *² 175 mL conical bottles from BD/Corning (352076). Please note that these conical bottles need to be used together with a conical form insert provided by the bottle manufacturer.

Ordering Information

Number of vessels per adapter/rotor	Order no.
9/54	5920 765 000
8/48	5920 763 008
7/42	5920 762 001
7/42	5920 764 004
4/24	5920 761 005
1/6	5920 761 005
1/6	5920 766 007
7/42	5920 769 006
7/42	5920 770 004
3/18	5920 767 003
1/6	5920 771 000
1/6	5920 768 000
	9/54 8/48 7/42 4/24 1/6 1/6 7/42 3/18 1/6

*3 Universal adapters for Eppendorf Tubes® 5.0 mL are required in addition (5820 732 008).

Your local distributor: www.eppendorf.com/contact

 $Eppendorf\,AG\cdot Barkhausenweg\,1\cdot 22339\,Hamburg\cdot Germany\\ eppendorf@eppendorf.com\cdot www.eppendorf.com$

www.eppendorf.com/next-benchmark

Corning® is a registered trademark of Corning Inc., USA. FACS® is a registered trademark of Becton Dickinson and Co., USA. Nalgene® oak ridge tubes is a trademark of Nalge Nunc International Corp., USA. Eppendorf®, the Eppendorf Brand Design, Eppendorf QuickLock® and Eppendorf Tubes® are registered trademarks of Eppendorf AG, Germany. All rights reserved, including graphics and images - Copyright © 2019 by Eppendorf AG. Order No. AA01 000 520/EN1/6T/0319/SSO/STEFF · Carbon neutrally printed in Germany.